



Oil Pro CLD-6

30% Silicone Emulsion Antifoam

PRODUCT DESCRIPTION:

Oil Pro CLD-6 is a water dispersible industrial antifoam containing 30% active ingredients. Oil Pro CLD-6 contains a combination of silicone polymer and dispersant, and has been found to exhibit superior foam control in systems over a wide range of operating temperatures (up to boiling).

APPLICATIONS AND SUGGESTED USAGE:

Oil Pro CLD-6 is designed to control foam in industrial applications. It is best to apply Oil Pro CLD-6 before foaming occurs and under agitation. Testing will be necessary to determine the optimal dosage rate.

- Industrial fermentation processes
- Waste water systems
- Adhesive processing
- Grease and oil processing
- Cleaning compounds
- Oil field drilling muds
- Petroleum processing
- Metalworking lubricants

TYPICAL PROPERTIES:

Appearance @ 25°C	White emulsion
Specific Gravity @ 25°C	0.99
Viscosity @ 25°C, cPs	2,400
pH	7.0

HANDLING AND STORAGE:

To ensure product quality, the product should be stored in sealed containers at temperatures between 40°F and 120°F. Shelf life for Oil Pro CLD-6 is one year from the date of manufacture. Oil Pro CLD-6 is available in drums, totes, and bulk quantities.

The information given herein is believed to be reliable, but no guarantee is made or liability assumed.

4010 La Reunion Parkway Suite 160 Dallas, TX 75212 • Phone: 214-638-2468