



Product Data Sheet

Product Description

Product Name: ProFlush OBD-22
Chemical Name: Cementing pre-flush
Company Name: ARC Products Inc
Address: 4010 La Reunion Parkway
Suite 160
Dallas, TX 75212
Telephone Number: (214) 638-2468

Product Applications

ProFlush OBD-22 was developed to provide excellent rinse off and water wetting when used as a pre-flush for oil based muds.

Typical Properties

Appearance	Light yellow to amber
pH, (5%w/w in DI water)	5.0 - 7.0
Density (lbs/gallon)	9.0
Specific gravity	1.08
Pour Point, °C	-17

Storage and Handling

Storage	Store the product away from sparks, flames or other heat sources. Keep containers closed. Even with a low pour point to ensure homogeneity of the product at low temperatures mix well before using.
Handling	Use appropriate personal protective equipment when working with ProFlush OBD-22. Do not get into eyes, on skin, ingest or inhale mist/vapor generated during the use of the product. Try to prevent the generation of mist/vapor during use of the product. Make sure that proper ventilation and eye washes/safety showers are present in the immediate work area. Do not flush product into the sewer system.

Date: 06/17/2022
Revision: New



Product Data Sheet

Product Performance

ProFlush OBD-22 was tested with a diesel based OBM that has a density of 13.4 pounds per gallon

<u>ProFlush OBD-22, %w/w</u>	<u>Viscosity @ 180°F, cps</u>	<u>Rinse off @ 180°F, %</u>	<u>ProFlush OBD-22, lbs per barrel</u>
1.8	8	90	
1.2		94	
0.8		97	

Date: 06/17/2022
Revision: New